

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>D04H 11/04</b>	<b>A1</b>	(11) International Publication Number: <b>WO 99/61693</b> (43) International Publication Date: 2 December 1999 (02.12.99)
<p>(21) International Application Number: PCT/CZ98/00025</p> <p>(22) International Filing Date: 25 May 1998 (25.05.98)</p> <p>(71) Applicant (for all designated States except US): I.N.T., KRČMA RADKO [CZ/CZ]; Karla Čapka 22, 460 05 Liberec 5 (CZ).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): <sup>1-00</sup> JIRSÁK, Oldřich [CZ/CZ]; Dobiášova 856/6, 460 06 Liberec 6 (CZ). <sup>2-00</sup> HANUŠ, Jaroslav [CZ/CZ]; Vanurova 819, 460 03 Liberec 3 (CZ). <sup>3-00</sup> KOTEK, Václav [CZ/CZ]; Karla Čapka 9, 460 05 Liberec 5 (CZ). <sup>4-00</sup> SANETRNÍK, Filip [CZ/CZ]; Malátova 430, 460 13 Liberec 13 (CZ). <sup>5-00</sup> KRČMA, Radko [CZ/CZ]; Karla Čapka 22, 460 05 Liberec 5 (CZ).</p> <p>(74) Agent: KUBÍKOVÁ, Kvetoslava; Rektorát CVUT, Patentové Středisko BIC CVUT, Žitná 4, 166 36 Praha 6 (CZ).</p>	<p>(81) Designated States: AU, BR, CA, ID, IL, JP, KR, TR, US, ZW, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report.</p> <p><i>Liberec</i> ← <i>city</i> <i>CZ</i> ← <i>all inventors</i></p>	

(54) Title: A DEVICE FOR PERPENDICULAR STRATIFICATION OF PLANARY FIBROUS SHAPES

## (57) Abstract

A device for perpendicular stratification of planary fibrous shapes, above all of fibrous web, comprising two synchronously moving elements, connected with the driving mechanism according to the invention consists in that the reciprocating moving elements (1, 2) are connected with their driving mechanism (3) indirectly by the intermediary of at least one robust shaft (4) rigidly fitted in bearings in a rigid framework of the machine, while one element (1) is connected with the shaft (4) rigidly or over flexible joints (6), and a second element (2) is coupled by means of flexible joints (7) with the same shaft or with another shaft. The driving mechanism (3) can consist of one driving shaft (8) with two crank assemblies (9) arranged with a phase shift to each other. The flexible joints (6 and 7) consist of flat steel springs with a width-to-thickness ratio more than 10.

